

LIFT-EZE

Lift Station Degreaser

OC 500

Liquids

OVERVIEW

Our Lift-EZE OC 500 keeps lift station surfaces free of grease. As waste water levels rise and fall, heavy grease deposits are deposited on lift station walls. It coats the walls and surfaces of the lift station to remove heavy grease accumulations quickly and safely. Our special non-emulsifying formula floats on the surface of the water, so it continues to remove deposits as the water level changes. Our unique formula contains a soybean oil derivative which does not evaporate as fast as other solvents, so it remains on the surface of wastewater longer to penetrate fats, oils, and grease (FOG), dirt and strip them away from the surfaces. This product will not disrupt the natural biological process of bacteria in the lift station.

DIRECTIONS:

Lift Stations: Use approximately ½ gallon of Lift-EZE for every square foot of wastewater surface area. This special floating formula washes down the sides of the lift station as the water level rises and falls

For circular lift stations calculate the square feet of water surface area using this formula:

CALCULATE:

$$3.145 \times r^2 = \text{surface area}$$

Note: r = radius of the lift station

APPLICATIONS & ADVANTAGES:

- I LIFT STATIONS
- I FLOATING GREASE BALLS
- I HEAVY OIL ACCUMULATION
- I ANNOYING ODORS
- I QUICKLY DISSOLVES HEAVY GREASE AND FAT ACCUMULATIONS ON LIFT STATION
- I CREATES AN ODOR ABSORBING BARRIER TO CONTROL ODORS AND LEAVES A PLEASANT CITRUS SCENT
- I 100% NATURAL AND BIODEGRADABLE FORMULA
- I COLOR INDICATION LETS YOU KNOW WHEN YOU NEED TO ADD MORE

LIFT-EZE

Lift Station Degreaser

OC 500

Liquids

TYPICAL PROPERTIES

I APPEARANCE	GREEN LIQUID
I FRAGRANCE	FRESH SCENT
I FORM	LIQUID
I SHELF LIFE	24 MONTHS
I pH	6.8 - 7.8
I EFFECTIVE TEMPERATURE RANGE.....	5° – 50° C
I SPECIFIC GRAVITY.....	0.88
I SOLUBILITY.....	INSOLUBLE IN WATER

PACKAGING

- I 1 GALLON, 4 X 1 GALLON CASE, 5 GALLONS, 30 GALLON, 55 GALLON