

It is the user's responsibility to determine conditions for use of this product and to assume liability for loss, injury, damage or expense resulting in improper use.

Storage and Handling: Store in a cool, dry location. Keep pail tightly closed with not in use. **CAUTION:** May irritate eyes. Avoid contact with eyes. Do not take internally. **FIRST AID: If In Eyes:** Wash thoroughly with water. **If Swallowed:** Give person several glasses of water and induce vomiting. Obtain medical assistance. **Skin Contact:** Wash area thoroughly with soap and water.

Do not ingest internally. Avoid skin contact. Wear rubber gloves when using this product. Wash thoroughly after handling. Storage: Store in a cool, dry place. Avoid contact with strong acids.

This information is believed to be accurate and reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control. For this reason we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage or use of this product.

HMS Rating - Health: 1, Fire: 0, Reactivity: 0, Personal Protection: B

KEEP OUT OF REACH OF CHILDREN



BP-1205

Food Processing Blend

Net Contents: 25 LBS.
1/2 LB | Water-Soluble Packets



Cumming, Georgia 30028 USA
(888) 886-1461
www.rex-bac-t.com

Lot#:

From the small food operations to large scale food processing plants where waste water is a major concern. The accumulation of fats, oils and grease, and high levels of BODs, makes it increasingly difficult to adhere to the environmental regulations governing the amount of waste that can be pumped into our sewers. Our 1205 contains surface tension depressants and penetrants that loosen and liquify heavy grease deposits, thereby assisting in their biodegradation.

DIRECTIONS FOR USE:

NOTE: For Optimum Results activate the bacteria and enzymes in warm water before using.

***Refer to product catalog sheet for full instructions including wastewater and sewer lateral dosing.**

Grease Traps/Holding Tanks/Drain Lines:

1. 1205 should be used every night before close. Before starting program it is recommended that you have your drain lines and grease trap cleaned.
2. In 2 to 5 gallons of lukewarm water (80-90 degrees F) stir in the correct amount 1205 product based on the size of your system (refer to product data sheet). After a few minutes the particles will settle leaving the active ingredient suspended in solution.
3. Distribute the solution down each drain/sink/etc that leads to the grease trap
4. Do not add to the drain line that is connected to the dishwasher (do not use where water temperature exceeds 130 degrees F).
5. If you mix a dose double the dose the next day.

Note: Discontinue use of bleaches and quaternary compounds.