

## General Instructions

Same Great Root Killing Product  
- Just Better Packaging!

### RootX Root Killer - General Square Funnel Jar Application Instructions using Funnel Attachment - 2 Pound or 4 Pound Jars:

1. Unscrew Lid from top of container.
  2. Take the mixing funnel/applicator and put the wide threaded end into the opening where the lid was in the square container.
  3. Rotate the mixing funnel/applicator clockwise screwing the mixing funnel into the square container so that it fits tightly.
  4. Grasping the bottom of the square container and the narrow end of the mixing funnel applicator, (putting a hand over the mixing funnel/applicator cap which is located at the narrow end of the mixing funnel/applicator), Rock the square container with the mixing funnel/applicator attached, back and forth for approximately one minute allowing the two dry components of RootX root killer to go into the funnel and then back into the square container several times.
  5. After the one minute mixing process you may then take the cap off the narrow end of the mixing funnel/applicator and pour the entire contents of the dry product mixture through the mixing funnel/applicator directly into a sewer cleanout or toilet bowl if a sewer cleanout is not available. Note: Only flush 2 pounds at a time if you are applying through a toilet. If more than 2 pounds of RootX is required you can add 2 more pounds directly after the 1st flush and repeat. You can also add directly to a septic tank or distribution box for treating leach fields. Use the same mixing procedure when applying RootX to septic tanks and leach fields.
- If applying directly to a septic tank there is no need to add additional water to the septic tank.*
6. Water activates the RootX product. Use 5 gallons of water per pound of RootX product. Refer below to "Additional RootX Application Suggestions and Tips" for amount of water required based toilet or clean-out method.




### Application Instructions With No Funnel Attachment:

1. Unscrew Lid from top of container.
2. Pour the contents into a small pail and MIX the two dry components from the jar until the color is uniform. DO NOT add any water to the pail.
3. Pour the entire contents of the dry product mixture directly into the sewer cleanout or toilet bowl if a sewer cleanout is not available. Note: Only flush 2 pounds at a time if you are applying through a toilet. If more than 2 pounds of RootX is required you can add 2 more pounds directly after the 1st flush and repeat.  
*You can also add directly to a septic tank or distribution box for treating leach fields. Use the same mixing procedure when applying to septic tanks and leach fields.*
4. Water activates the RootX product. Use 5 gallons of water per pound of RootX product. Refer below to "Additional RootX Application Suggestions and Tips" for amount of water required based toilet or clean-out method.



Tel. (888) 886-1461

www.rex-bac-t.com



## General Instructions

Same Great Root Killing Product  
- Just Better Packaging!

### RootX® Root Killer Treatment Guide: Quantity of RootX® Required:

- Quantity of RootX root killer required is based on the total feet from the start of the application (Example: Toilet or Clean Out) to beyond the point of root intrusion or to the city sewer connection at the street (see chart below).
- 2lb. jar will treat a maximum 50ft. of 4-inch pipe
- 4lb. jars will treat approximately 100ft. of 4-inch pipe or 75ft. of 6-inch pipe

Method	RootX Amount	Pipe Diameter	Length
Septic Tanks	8 lb. per 1,000 gals.		
RootX Jars	2 lb. Jar	4 inch	50 feet
RootX Jars	4 lb. Jar	4 inch	100 feet
RootX Jars	4 lb. Jar	6 inch	75 feet

After application, you should limit water use for at least 4-6 hours, allowing time for roots to absorb the RootX.

### Additional RootX Application Suggestions and Tips:

- Put no more than 2lbs of RootX in a toilet bowl at a time to minimize possibility of foam overflow!
  - When applying into a sewer clean out, apply 5 gallons of water per pound of RootX product to ensure that the foam is pushed completely down the sewer line. After adding the RootX dry powder mixture to the toilet or clean out you can use a 5 gallon pail to add the correct amount of water.
- Tip:** If applying RootX through a sewer cleanout you can use your bathtub to flush the correct amount of water down the pipe to ensure the RootX foam is pushed down the pipe. Example: If you are treating 40 feet of 4" diameter pipe then use 2 pounds of product. Fill your bathtub that leads to the clean-out with 10 gallons of water (this would be 5 gallons per pound of product). Pour mixed dry RootX powder in the cleanout. Cap the cleanout. Then release the water in your bathtub. Restrict water for 4-6 hours.
- When applying into the toilet have one hand on the flush handle, start adding the dry mixture into the toilet bowl then flush. Try to get the product down in the 1st flush.
- It is suggested that when doing a toilet application, that you have a 5 gallon bucket filled with water readily available to pour in the toilet. Pour the water in the toilet after flushing to push the foam down the toilet drain. This will help avoid any possibility of foam overflowing the bowl.
- If you are applying through a toilet, the required water can be applied with a 5 gallon pail directly to the toilet or flush the toilet the required amount of times (up to 6 times for a 1.6 gallon low flow toilet when applying 2 pounds of RootX product).
- **Restrict water usage from 4 - 6 hours after application.**

**DO NOT STORE FOR FUTURE USE!**

Entire contents of container must be used on application.

www.rex-bac-t.com